|                            |    |  |             | Doc No         |      |
|----------------------------|----|--|-------------|----------------|------|
| BALRANALD SHIRE<br>COUNCIL | BU | ILDING SETBACK                                       |             | Version<br>1.1 | Date |
| Controller:                |    | Approved By:   | Review Date |                |      |
| GENERAL MANAGER            |    | Council DATE 21 August 2018<br>Minute No: 08.18.4387 | May 2020    |                |      |

**OBJECTIVES:** To specify minimum setback distances to apply in particular circumstances.

## **POLICY STATEMENT**

- 1. A general residential building line setback of 6m minimum, measured from the primary street boundary, applies for all roads and streets.
- 2. A setback in accordance with Table 1 applies to the secondary street frontage on corner allotments.
- 3. In residential cul-de-sacs with width of no more than 13m a residential building line setback of minimum 4m in the straight area and minimum 3m in the turning area applies.
- 4. Residential building line setbacks may be reduced by Council in exceptional circumstances.
- 5. Building line setbacks for other than residential land use will be established by Council on a case by case basis in accordance with the planning instrument.

## Table 1

| Lot size       | Minimum setback from secondary road boundary |
|----------------|--|
| 200m2-600m2    | 2m   |
| >600m2-1,500m2 | 3m   |
| >1,500m2       | 5m   |